

HYDROTAP G5 INDUSTRIAL SIDE TOUCH BOILING CHILLED 160/175





BOILING

CHILLED

FILTERED

Order Code H5J704Z00UK

Discover the Zip Water HydroTap Industrial Side Touch, providing instant filtered boiling and chilled tap water for your office or workplace.

Manufacturing Code	H5J704Z00UK
Capacity	Commercial
Number of people	60
Boiling Cups per hour	160
Chilled Cups per hour	175
Chilled Litres per hour	175



Тар	HydroTap Industrial Side Touch bright chrome
Water Pressure	Min 1.7 bar - Max 5 bar
Water Connection	1/2" BSP
Water Supply Requirements	Cold
Water Valves	Integrated dual check valve
Power Rating	2.1kW 230v 50/60 Hz
Power Supply	1 x 13 amp
Dimensions	W500mm x D520mm x H373mm
Product Approvals	CE, UKCA
Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

^{&#}x27;1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'