


- **Maximum cooling capacity** 2,6kW**/10.500 Btu/h*
- **Low Energy Consumption** Class A
- **Eco-friendly gas** R290
- **Quiet Function** 37% noise reduction

- Fan function
- Dehumidifying function
- Exclusive condensate recirculation system
- 3 fan speed to select the maximum power or the minimum noise
- Soft touch control panel
- Remote control with LCD display allows an easy use of all features
- 24h electronic timer and thermostat
- Handles and castors for easy transportation
- Continuous gravity drainage system



EFFICIENCY

Perfect match of most advanced technology and low consumption, Pinguino PAC EM achieves **A class of Energy Efficiency**.

NEW ECO-DESIGN

Featuring a stylish and innovative design, Pinguino PAC EM is kind to the environment

696 TIMES ECO-FRIENDLY

Pinguino PAC EM uses the **refrigerant gas R290**, which is up to 696 times more environmentally friendly than traditional gases***

Quiet TECHNOLOGY

The silence of power. Pinguino EM90, up to **37% MORE Quiet****** thanks to DL technology

SOFT TOUCH CONTROL PANEL

PAC EM has an user-friendly soft-touch control panel for an easy use of all desired functions.

TECHNICAL DATA

Maximum cooling capacity	BTU/h* – Kw**	10.500 – 2,6
Energy Efficiency Ratio (EER)**	(W/W)	2,6
For rooms up to	m ³	90
Refrigerant gas		R290
Energy Efficiency Class		A
Rated voltage – frequency	V~Hz	220-240~50
Input power**	W	1000
Maximum sound power level**	dB(A)	63
Noise pressure level (min-max)	dB(A)	47/50
Air flow(min-med-max)	m ³ /h	340/370/400
Max dehumidifying (dehum. Mode at 30°C /80%RH)	l/24h	50
Dimensions (hxlxp)	mm	700x425x345
Net Weight	Kg	31,5

•* 35°C/80% R.H.

•** 35°C/40% R.H. (EN14511)

***696 times

compared to the impact of Global Warming of R410 - F-Gas Reg. 517/2014.

**** Tested in our laboratory by comparing the **Power Noise at max. fan speed vs Power Noise at Quiet function in cooling mode**

